

Delphion

RESEARCH

INTEGRATED IAM

SERVICES

INSIDE DELPHION

[Log Out](#) [Work Files](#) [Saved Searches](#)[My Account](#) | [Products](#) | [News](#) | [Events](#)Search: [Quick/Number](#) [Boolean](#) [Advanced](#)[Help](#)

The Delphion Integrated View

Buy Now: [More choices...](#)Tools: Add to Work File: [Create new Work File](#) View: [INPADOC](#) | Jump to: [Top](#) ☒ [Go to: Derwent...](#)☐ [Email this to a friend](#)Title: **JP11317232A2: FLAME RETARDER OF ELECTROLYTE FOR LITHIUM BATTERY**Country: **JP** JapanKind: **A2** Document Laid open to Public inspectionInventor: **UE MAKOTO;**Assignee: **MITSUBISHI CHEMICAL CORP**
[News, Profiles, Stocks and More about this company](#)Published / Filed: **Nov. 16, 1999 / April 5, 1999**Application Number: **JP1999000097105**IPC Code: **H01M 6//16; H01M 10//40;**Priority Number: **April 5, 1999 JP1999000097105**
April 5, 1999 JP1999199997105

Abstract:


PROBLEM TO BE SOLVED: To provide an electrolyte having flame retardance while maintaining battery characteristics by including trialkyl phosphate.

SOLUTION: Trialkyl phosphate giving flame retardance to an electrolyte is represented by formula I. In the formula, R1-R3 are the same or different straight-chain or branched alkyl group having 1-4 carbon atoms. Specifically trimethyl phosphate and dimethyl phosphate may be mentioned. The content of the phosphoric ester in the electrolyte depends on the capacity requirement of a battery, but when the whole amount of the solvent is replaced by the phosphoric ester, the flame retardance of the battery is maximized. For increasing the flame retardance by adding to the electrolyte as an assistant solvent, 15 wt.% or more phosphoric ester is preferable, and addition of 30 wt.% or more phosphoric ester is more preferable. As the solvent for mixing, ethylene carbonate, for example, is mentioned.

COPYRIGHT: (C)1999,JPO

Family: [Show 2 known family members](#)Other Abstract: **None**

Info:

[Nominate](#)[this for the Gallery...](#)[View Image](#)

1 page



(19)

(11) Publication number: **11317232 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **11097105**(51) Intl. Cl.: **H01M 6/16 H01M 10/40**(22) Application date: **05.04.99**

(30) Priority:

(43) Date of application
publication: **16.11.99**(84) Designated contracting
states:(71) Applicant: **MITSUBISHI CHEMICAL CORP**(72) Inventor: **UE MAKOTO**

(74) Representative:

**(54) FLAME RETARDER OF
ELECTROLYTE FOR
LITHIUM BATTERY**

(57) Abstract:

PROBLEM TO BE SOLVED: To provide an electrolyte having flame retardance while maintaining battery characteristics by including trialkyl phosphate.

SOLUTION: Trialkyl phosphate giving flame retardance to an electrolyte is represented by formula I. In the formula, R1-R3 are the same or different straight-chain or branched alkyl group having 1-4 carbon atoms. Specifically trimethyl phosphate and dimethyl phosphate may be mentioned. The content of the phosphoric ester in the electrolyte depends on the capacity requirement of a battery, but when the whole amount of the solvent is replaced by the phosphoric ester, the flame retardance of the battery is maximized. For increasing the flame retardance by adding to the electrolyte as an assistant solvent, 15 wt.% or more phosphoric ester is preferable, and addition of 30 wt.% or more phosphoric ester is more

preferable. As the solvent for mixing, ethylene carbonate, for example, is mentioned.

COPYRIGHT: (C)1999,JPO

